



AUTO FEED SCREW DRIVERS
AND COLLATED FASTENERS

FDVL42 - SPEED DRIVER

The FDVL42 Auto Feed Screw Driver is the workhorse of our stable of drivers. **Decks, Docks, Cement board, Sub Floors and Underlayment** installs are a breeze with 150 easy-load screw coils and easy adjustable T-handle for standup operation.

- Adjustable depth control for repeatable countersinking
- Drives 1" to 3" screws (#6, #8 & 10)
- No pre-drilling required even in Exotic Hardwoods like IPE
- No more dropped or lost screws
- 150 screws per easy load coil
- Work while standing up. Less stress on back and knees
- The tool stands on its own when not in use

Customer Support That Counts

When you work with our tools you are backed not only by the industry standard for power, speed, and quality but you have access to our extensive line of fasteners and our knowledgeable customer service staff. Pick up the phone or send an email anytime with questions about the right tools or fasteners for your job and we'll get you on the right track. Our priority is ensuring that your job gets done right.



For specifications and a full list of our tools, screws and specialized fasteners visit our web site

www.muro.com

MURO NORTH AMERICA INC.
7 Tilbury Crt., Brampton, ON., Canada L6T 3T4
productinfo@muro.com or 1 800 665 6876



Specifications

Speed: 2300 RPM, 2800 RPM or 3500 RPM **Voltage:** 115V **Current:** 5.2A **Screw Range:** 1" to 3"

Accessories: Telescopic Extension Handle **Driver Bits:** Double ended, lasts twice as long: **SQR27114** (Square Drive #2), **PHL27114** (Phillips Drive #2), **TX207114** (Torx Drive #20), **TX257114** (Torx Drive #25)

Visrope® Collated Screw Coils - FDVL42

Drywall Screws

Recess	Thread	Coating	Available Size	Application
Phillips	Fine	Black Phosphate	1, 1-1/4, 1-5/8, 2, 2-1/4, 2-1/2, 3	Drywall or wood to light gauge steel
Phillips	Coarse	Black Phosphate	1, 1-1/4, 1-5/8, 2, 2-1/4, 2-1/2	Drywall or wood to wood
Phillips	Self Drill	Bright Zinc	1-1/4, 1-5/8, 2, 2-3/8, 3	Drywall or wood to heavy gauge steel

Sub Floor & Underlayment Screws

Recess	Thread	Coating	Available Sizes	Application
Square	Coarse	Yellow Zinc	1, 1-1/4	Wood to wood
Square	Fast Pitch Twin	Yellow Zinc	1-1/2, 1-3/4, 2, 2-1/2, 3	Wood to wood
Phillips	Coarse	Yellow Zinc	1-1/4, 1-1/2, 1-3/4, 2, 2-1/2	Wood to wood
Square	Self Drill	Bright Zinc	1-1/4, 1-1/2, 2	Wood To Steel
Square	Hi-Lo	Yellow Zinc	1-1/4	Wood To wood

Cement Board Screws

Recess	Thread	Coating	Available Sizes	Application
Square	Coarse	Silver Ceramic	1-1/4, 1-3/4	Cement backer board to wood
Square	Self Drill	Silver Ceramic	1-5/8	Cement backer board to steel

Deck & Dock Screws

Recess	Thread	Coating	Available Sizes	Application
Square	Coarse	Green Epoxy	1-1/4, 1-1/2, 1-3/4	Decking to wood
Square	Fast Pitch Twin	Green Epoxy	2, 2-1/2, 3	Decking to wood
Square	Fast Pitch Twin	Gray Epoxy	2-1/2, 3	Decking to wood
Square	Coarse	Brown Epoxy	2-1/2, 3	Decking to wood
Square	Coarse	305 Stainless	1-1/8, 1-3/4, 2, 2-1/2, 3	Decking to wood
Square	Coarse	316 Stainless	2, 2-1/2, 3	Decking to wood

Composite Deck Screws – Shroomless Fastening for Composite Decking

Recess	Thread	Coating	Available Sizes	Application
Torx	Shroomless	Tan, Gray & Brown Ceramic	2-1/2	Composite decking to wood
Torx	Shroomless	Stainless Steel	2-1/2, 3	Composite decking to wood

Trim Head Screws

Recess	Thread	Coating	Available Sizes	Application
Square	Coarse	Silver Ceramic	2-1/4, 3	Composite decking or wood to wood
Square	Coarse	Stainless Steel	2-1/2, 3	Composite decking or wood to wood

Ejector Hardwood Screws – Fastens Ipe, Cumaru and others without pre-drilling

Recess	Thread	Coating	Available Sizes	Application
Square/Torx	Ejector	305 Stainless	1-1/2, 2, 2-1/2, 3	Exotic hardwood decking to wood

For specifications and a full list of our tools, screws and specialized fasteners visit our web site

www.muro.com

1-800-665-6876

MURO NORTH AMERICA INC.

7 Tilbury Crt., Brampton, ON., Canada L6T 3T4
productinfo@muro.com or 1 800 665 6876